Fanvil i63 Video Door Phone

Overview

The i63 Video Door Phone integrates access control, intercom, and security into a sleek, modern station. Refined craftsmanship blends a high-tech aesthetic with an excellent user experience. Rated IP66 and IK07, it ensures robust protection against harsh weather and impact. A 2MP camera and 5 speed-dial buttons enable clear, instant video calls, while flexible access methods simplify entry management. Compatible with SIP and ONVIF, the i63 fits seamlessly into existing systems, providing reliable solutions for high-end apartments, office buildings, residential communities, and industrial parks.

Features

- 5 customable speed-dial buttons for instant calling
- Integrated 2 MP HDR camera for clear and detailed imaging
- IP66 and IK07 rated for all-weather reliability
- Versatile interfaces for seamless security system integration
- ONVIF-compliant for high flexibility and compatibility



Fanvil Link Technology Co., Ltd.
Add: 13th Floor, Building 2, Runzhi R&D Center, Xin'an Street, Bao'an District, Shenzhen, China
Phone: 0755-26402199 E-mail: sales@fanvil.com Web: www.fanvil.com

Specification

Applications	Townhouse, offices, small apartments
Keypad	5 speed-dial buttons with customizable labels
Casing Material	Aluminum alloy
Color	Gunmetal gray
Image Sensor	1/2.9" CMOS
Camera	2MP
FOV	120° (horizontal), 60° (vertical)
Video Codec	H.264 (baseline profile & main profile)
Min. Illumination	0.1 Lux, IR illumination supported
Card Capacity	10,000
Power Consumption	PoE: 1.70–6.94 W; Power adapter: 1.50–6.02 W
Power Supply	12 VDC, 1 A; PoE: 802.3af Class 3
Operating Temperature	−40 °C to +70 °C (−40 °F to +158 °F)
Storage Temperature	−40 °C to +70 °C (−40 °F to +158 °F)
Product Dimension	177.4 mm × 88.0 mm × 36.15 mm (6.98" × 3.46" × 1.42") (L × W × H)
Protection Rating	IP66; IK07
Installation	Wall mounting; Flush mounting with EX102 bracket (sold separately)
Gross Weight (G.W)	0.69 kg
Package Dimensions	Gift box: 220.0 mm × 123.0 mm × 65.0 mm (8.66" × 4.84" × 2.56") (L × W × H); Outer CTN: 463.0 mm × 350.0 mm × 266.0 mm (18.23" × 13.78" × 10.47") (L × W × H)
QTY/CTN	20 pcs

Functions

Supported Protocols	SIP 2.0 over UDP/TCP/TLS
Access Methods	IC/ID card, DTMF code, App
Interfaces	3 short-circuit inputs; 2 short-circuit outputs; 1 Wiegand interface (26/34); 1 RS-485 (reserved); 1 line out for induction loop
ONVIF	Profile S
Card Types	MIFARE: MIFARE Classic 1K/4K, MIFARE DESFire, MIFARE Ultralight, MIFARE Plus; Frequency: 13.56 MHz, 125 kHz
Talking Mode	Full-duplex (HD audio)
Additional Functions	Built-in relay, open API, motion detection, tamper alarm, TF card